# **Product datasheet**

Specifications

Sreen Premium<sup>™</sup>



## EasyLogic - Digital Panel Meter DM1000 - Frequencymeter - single phase

METSEDM1310

#### Main

| Range                     | EasyLogic                                   |
|---------------------------|---|
| Product Name              | EasyLogic DM1000                            |
| Device Short Name         | DM1310                                      |
| Product Or Component Type | Frequency meter                             |
| Device Application        | Test laboratories<br>Load control<br>GenSet |

#### Complementary

| · · · · · · · · · · · · · · · · · · |  |
|-------------------------------------|--|
| Poles Description                   | 1P + N   |
| Type Of Measurement                 | Frequency  |
| [Us] Rated Supply Voltage           | 100230 V AC +/- 20 %<br>100230 V DC +/- 20 %                               |
| Supply Frequency                    | 50/60 Hz +/- 5 Hz  |
| Network Frequency                   | 60 Hz<br>50 Hz   |
| Maximum Power Consumption In<br>Va  | 3 VA at 230 V AC   |
| Display Type                        | LED  |
| Display Digits                      | 4  |
| Full Scale Display                  | 99.99  |
| Frequency Measurement Range         | 20100 Hz 25277 V AC phase to neutral<br>20100 Hz 44480 V AC phase to phase |
| Accuracy                            | Frequency +/- 0.2 % of full scale  |
| Device Mounting                     | Flush  |
| Mounting Support                    | Panel  |
| Type Of Installation                | Indoor   |
| Measurement Category                | Category III   |
| Standards                           | IEC 61326  |
| Product Certifications              | CE conforming to IEC 61010-1   |

#### Environment

| Electromagnetic Compatibility            | Conducted and radiated emissions class A conforming to CISPR 11<br>Electrostatic discharge conforming to IEC 61000-4-2<br>Electrical fast transient/burst immunity test conforming to IEC 61000-4-4<br>Surge immunity test conforming to IEC 61000-4-5<br>Conducted RF disturbances conforming to IEC 61000-4-6<br>Magnetic field at power frequency conforming to IEC 61000-4-8<br>Voltage dips and interruptions immunity test conforming to IEC 61000-4-11<br>Harmonics conforming to IEC 61000-3-2<br>Limitation of voltage changes, voltage fluctuations and flicker in low-voltage<br>conforming to IEC 61000-3-3 |
|--|---|
| Ip Degree Of Protection                  | Front panel: IP50<br>Body: IP30   |
| Relative Humidity                        | 595 %   |
| Pollution Degree                         | 2   |
| Ambient Air Temperature For<br>Operation | -1060 °C  |
| Ambient Air Temperature For<br>Storage   | -2570 °C  |
| Colour                                   | Black   |
| Width                                    | 96 mm   |
| Height                                   | 96 mm   |
| Depth                                    | 38 mm   |
| Cut-Out Dimensions                       | 92 x 92 mm  |
| Net Weight                               | 160 g   |

## **Packing Units**

| Unit Type Of Package 1       | PCE     |
|------------------------------|---------|
| Number Of Units In Package 1 | 1       |
| Package 1 Height             | 9.6 cm  |
| Package 1 Width              | 9.6 cm  |
| Package 1 Length             | 4.35 cm |
| Package 1 Weight             | 256 g   |
| Unit Type Of Package 2       | \$03    |
| Number Of Units In Package 2 | 16      |
| Package 2 Height             | 30 cm   |
| Package 2 Width              | 30 cm   |
| Package 2 Length             | 40 cm   |
| Package 2 Weight             | 4.1 kg  |
| Unit Type Of Package 3       | P06     |
| Number Of Units In Package 3 | 128     |
| Package 3 Height             | 105 cm  |
| Package 3 Width              | 60 cm   |
| Package 3 Length             | 80 cm   |
| Package 3 Weight             | 32.8 kg |

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

#### Well-being performance

Rohs Exemption Information

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |